



SPORT STOCK

~~Measurement Diagram 2007~~

- A - door post must meet outside of car
- B - max height 3"
- C - 78" middle bar of door max
- D - 76" top and bottom of door max
- E/ outside of rear tire to outside of rear tire, 86"max
- F/ trunk level for 32" from spoiler
- G/ 74" max width middle of rear of car
- H/ 72" max width spoiler & bottom of rear of car
- I/ 45 min. 52" max front to back of roof
- J/ 46 min. 52" max side to side of roof
- K/ 40" max center of hub to front of bumper
- L/ 33" max height of hood and fenders from ground
- M/ 48" max height of roof
- N/ 16" max length of bottom of side vent then straight up
- O/ 105" minimum wheel base
- P/ 52" max center of rear hub to top corner of quarter panel
- Q/ 38" max top of trunk to ground
- R/ 42" max top of spoiler to ground
- S/ 12" max top of rear roof support W/no window
- S/ 24" max bottom of rear roof support W/no window
- T/ 40" max bottom of rear roof support W/no window
- U/ 17" max top of rear roof support W/window
- V/ top of rear roof support must meet bottom at an angle to point
- W/ 18" max bottom of rear spoiler (entire spoiler on trunk surface)
- X/ 4" max height of rear spoiler support
- Y/ 22" top of rear spoiler support at angle top to bottom
- Z/ must see outside tread of front tire from front of car



Measurement Diagram 2007

